

TOTO LINK

www.totolink.net

The Smartest Network Device



600Mbps
Wireless Ceiling
Mount AP

Model No. **CA600-POE**



600 Mbps
802.11b/g/n



Long Range



Ceiling Design



Multiple SSID

➤ Overview


600Mbps Wireless Ceiling Mount AP

Model No. **CA600-POE**

TOTOLINK CA600-PoE is a sleek white wireless ceiling mount AP. It complies the IEEE 802.11n Wi-Fi standard. With the 4T4R MIMO technology, the AP delivers speeds up to 600Mbps.

Medium-power feature allows it to produce strong signals to penetrate walls and extend Wi-Fi over large areas.

The special 4T4R design reduces interferences, ideal for various scenarios especially smart homes.




➤ Features

- Up to 600Mbps data rate for Wi-Fi network.
- Complies with the 802.11n Wi-Fi standard
- Adopts the 4T4R MIMO technology
- 802.3af/at compliant PoE for simple deployment and low cost
- Handles up to 32 Wi-Fi connections simultaneously
- Two options, local device management and remote AC central control, are available
- Provides 64/128-bit WEP, WPA, WPA2 and WPA/WPA2 (TKIP+AES) security.
- Reboot Schedule provides better stability.
- More clear working status with three colors of LED.

Selling point

600Mbps 11N Ultra-fast Wi-Fi

With the 4T4R MIMO technology, CA600-PoE delivers speeds up to 600Mbps and is backwards compatible with older standards like 802.11b and 802.11g.



Wide Wi-Fi Coverage

Medium-power feature makes it possible for wide coverage over large areas and a stable wireless connection to the Internet.




Concurrent Multiple SSIDs

Multi-SSID feature allows user to create and configure multiple different wireless networks (SSIDs) so that each provides the proper level of access to connected clients.



IEEE 802.3af/at Compliant PoE

Compliant with 802.3af/at PoE, CA600-PoE can be powered by standard PoE switches, improving the deployment flexibility and reducing costs.



Specification

Hardware

Interface	- 1 * 100Mbps PoE port (Auto MDI/MDIX)
Button	- 1 * RST button
Power Supply	- IEEE 802.3af/at compliant PoE
LED	- 1 * SYSTEM LED (three colors)
Antenna	- 4 * internal antennas
Dimensions (D x H)	- 7.9 x 1.4 in. (200 x 35 mm)

Wireless

Standards	- IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
RF Frequency	- 2.4~2.4835GHz
Data Rate	- 802.11n: up to 300Mbps - 802.11g: up to 54Mbps - 802.11b: up to 11Mbps
EIRP	- < 20dBm
Wireless Security	- 64/128-bit WEP, WPA, and WPA2
Reception Sensitivity	- 11b: < -81dBm - 11g: < -68dBm - 11n: HT20 < -65dBm HT40 < -62dBm

Others

Package Contents	- CA600-POE Wireless Ceiling Mount AP*1 - Ethernet Cable *1 - Quick Installation Guide *1
Environment	- Operating Temperature: 0℃~50℃ (32℉~122℉) - Storage Temperature: -40℃~70℃ (-40℉~158℉) - Operating Humidity: 5%~95% non-condensing - Storage Humidity: 5%~95% non-condensing

ZIONCOM (HK) TECHNOLOGY LIMITED

Copyright ©ZIONCOM (HK) TECHNOLOGY CO., LTD. All Rights Reserved.

Headquarter & R&D Center

7/F, Unit D, 4 Building Shenzhen Software Industry Base, Xuefu Road,
Nanshan District, Shenzhen, Guangdong, China

Tel : +86-755-3686-1138 | FAX : +86-755-3686-1139

Factory

Building A1 & A2 Lantian Technology Park, Xinyu Road, Xinqiao Henggang Block,
Shajing Street, Baoan District, Shenzhen, Guangdong, China

Tel : +86-755-3686-1188 | FAX : +86-755-3686-1133

CA600-POE

600Mbps
Wireless Ceiling Mount AP