

The Smartest Network Device

USB 3.0 with RJ45 2.5G **Ethernet Adapte**

U2500 is a USB 3.0 with RJ45 2.5G Ethernet Adapter which allows users to connect to a wired network by plugging it into the computer's available USB.

U2500



USB 3.0 port



Lightweight



2.5G **Ethernet Port**







Overview

U2500 is a USB 3.0 with RJ45 2.5G Ethernet Adapter which allows users to connect to a wired network by plugging it into the computer's available USB. It can deliver high transmission rate that is ideal for speeding up data transfers between network servers and other computers, such as video conferencing.



Features

- 2.5G(10/100/1000/2500Mbps) Ethernet Port
- USB 3.0 port, 10 times the transfer rate of USB 2.0
- Plug & Play with Increased Compatibility
- Lightweight & Super Portable
- Connects PC to Any Ethernet Network Through Any USB Port
- Replace the Bad Ethernet Port
- Compatible with W and Linux 4.XX
 *Manual driver insta Linux 4.XX



- Compatible with Windows XP/Vista/7/8/8.1/10/11, Mac OS 10.6~10.14

*Manual driver installation is required for Mac OS 10.6~10.14 and

Specifications

General	
Chipset	- RTL8156BG-CG
Standards	- IEEE 802.3/802.3u, 802.3ab, 802.3bz
Port	- RJ45 2.5G LAN Port - 10/100/1000/2500Mbps
	- USB-type-A 3.0 Port x 1
Extended USB Cable	- 20 cm (excluding cable gland)
LED Indicator	- Blue LED Link/Act x1, 1G x 1, 2.5G x 1
Dimensions (L x W x H)	- 98 x 30 x 17.5mm
Others	
Package Contents	- U2500 Ethernet Adapter *1
	- Quick Installation Guide *1

Others

System Requireme

Environment

ZIONCOM (HK) TECHNOLOGY LIMITED Copyright©ZIONCOM (HK) TECHNOLOGY CO., LTD. All Rights Reserved.

Headquarter & R&D Center	7/F, Unit D, 4 Building Shenzhen Software Industry Base, Xuefu Road, Nanshan District, Shenzhen, Guangdong, China
Factory	Building A1 & A2 Lantian Technology Park, Xinyu Road, Xinqiao Henggang Block, Shajing Street, Baoan District, Shenzhen, Guangdong, China

nent	-Windows XP/Vista/7/8/8.1/10/11
	- Mac OS 10.6~10.14
	- Linux 4.XX
	- Operating Temperature: 0°C~50 °C (32 °F~122°F)
	- Storage Temperature: -40°C~70 °C (-40 °F~158°F)
	- Operating Humidity: 10%~90% non-condensing
	- Storage Humidity: 5%~90% non-condensing

Tel : +86-755-3686-1138 | FAX : +86-755-3686-1139

Tel : +86-755-3686-1188 | FAX : +86-755-3686-1133